



Better than it has to be®

1601 McCloskey Boulevard  
Hookers Point - Tampa, Florida 33605 U.S.A.  
E-MAIL: info@amalie.com  
www.amalie.com

Telephone: (813) 248-1988

Telecopier: (813) 248-1488

Compounding  
Blending  
Blow Molding  
Packaging

## MATERIAL SAFETY DATA SHEETS

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**GENERIC NAME:** Gas Treatment **ISSUE DATE:** JANUARY 2011

**TRADE NAMES:**

- 1. GREASED LIGHTNING  
GL4000 Fuel System Treatment

**CAS NUMBER:** Mixture  
**24 HOUR EMERGENCY TELEPHONE:** (CHEMTREC) 1-800-424-9300  
**TECHNICAL INFORMATION:** 813-248-1988

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENTS	CAS NO.	%	HAZARD DATA
Light Naphthenic Hydrotreated Distillates AFD 2575	64742-53-6	+/- 85	Exposure limits not considered
	Proprietary Blend	+/- 15	See section 15 for more info

### 3. HAZARDOUS IDENTIFICATION

<b>ROUTES OF ENTRY:</b>	Inhalation, Ingestion, Eye Contact, Skin Contact, Absorption
<b>TARGET ORGANS:</b>	Eyes, Skin, Central Nervous System, GI Tract, Respiratory System, Lungs
<b>MEDICAL CONDITIONS GENERALLY AGGREGATED BY EXPOSURE:</b>	Eye Disorders, Skin Disorders, Liver or Kidney Disorders
<b>CANCER INFORMATION:</b>	See section 15

### 4. FIRST AID MEASURES

<b>EYES:</b>	In case of contact, immediately flush with plenty of water for at least 15 minutes. Consult a physician.
<b>DERMAL:</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothes and shoes. Wash clothing before re-use.
<b>INGESTION:</b>	Call a physician. If swallowed, if conscious, give large amounts of water. Induce vomiting.
<b>INHALATION:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

### 5. FIRE FIGHTING MEASURES

**FLASH POINT, (Closed Cup) °C( °F):** ~120°F (48°C)

**FLAMMABLE LIMITS (% BY VOLUME):** **LOWER:** \_\_\_\_\_ **UPPER:** \_\_\_\_\_

**EXTINGUISHING MEDIA:** Use alcohol foam, dry chemical or carbon dioxide (Water may be ineffective.)

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece operated in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

**AUTOIGNITION TEMPERATURE:** ND

**EXPLOSION DATA:** Vapors may flow along surfaces to distant ignition sources and flash back. Contact with strong oxidizers may cause fire. Burns with a clear, almost invisible flame.

**NFPA RATING:** **HEALTH:** 1 **FLAMMABILITY:** 2 **REACTIVITY:** 0

**6. ACCIDENTAL RELEASE MEASURES**

**SPILL PROCEDURES:** Remove all ignition sources. Stop leak if you can do it without risk. Ventilate area and avoid breathing vapor or mist. Contain away from surface waters and sewers. Contain as a liquid for possible recovery or sorb with compatible sorbent material and shovel into collapsible container for disposal.

**7. HANDLING AND STORAGE**

**HANDLING PROCEDURES:** Keep away from intense heat, sparks, or flame. Empty containers may contain product residue which could include flammable or explosive vapors.

**STORAGE PROCEDURES:** Keep container tightly closed. Store in a cool, dry, well-ventilated, flammable liquid storage area.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

<b>ENGINEERING CONTROLS:</b>	Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits.
<b>GLOVES PROTECTION:</b>	Where skin contact is likely, wear Neoprene, Nitrile, or equivalent gloves; use of natural rubber or equivalent gloves is not recommended.
<b>EYE PROTECTION:</b>	Safety goggles, or chemical splash goggles if splashing is anticipated.
<b>RESPIRATORY PROTECTION:</b>	If high vapor or mist concentrations expected –(CONFINED OR RESTRICTED AREA) use respirator approved for organic vapors and mists.
<b>CLOTHING RECOMMENDATION:</b>	Wear appropriate chemical-resistant apron or other protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE:</b>	Amber
<b>ODOR:</b>	Slight Aromatic
<b>pH:</b>	NA
<b>VAPOR PRESSURE, mm Hg (20 °C):</b>	N/A
<b>VAPOR DENSITY:</b>	1.11 (Air=1)
<b>MELTING POINT, at 760 mm Hg:</b>	-98°C (-144°F)
<b>BOILING POINT, 760 mm Hg:</b>	320°F
<b>SOLUBILITY IN WATER:</b>	NEGLIGIBLE
<b>SPECIFIC GRAVITY:</b>	.889 (H2O = 1)
<b>EVAPORATION RATE:</b>	SLOWER THAN ETHER
<b>PERCENT VOLATILE (20°C):</b>	NE

**10. STABILITY AND REACTIVITY**

<b>STABILITY:</b>	Stable
<b>INCOMPATIBILITY:</b>	Strong oxidizing agents
<b>POLYMERIZATION:</b>	
<b>THERMAL DECOMPOSITION:</b>	Under normal conditions hazardous decomposition products should not be produced.

**11. TOXICOLOGICAL INFORMATION**

<b>EYE CONTACT:</b>	Irritation, may cause temporary corneal damage.
<b>DERMAL IRRITATION:</b>	Irritation, prolonged contact may cause dermatitis.
<b>INHALATION:</b>	Is harmful and may be fatal, headache, nausea, vomiting, dizziness, respiratory failure, low blood pressure, central nervous system depression.
<b>INGESTION:</b>	Is harmful vomiting may result, pulmonary aspiration possible.
<b>CHRONIC EXPOSURE</b>	Prolonged/repeated exposure has been associated with brain and nervous system damage

**12. HEALTH INFORMATION**

No	<b>HIGHLY TOXIC</b>	No	<b>SENSITIZER</b>
Yes	<b>TOXIC</b>	No	<b>REPRODUCTIVE EFFECTS</b>
No	<b>CORROSIVE</b>	No	<b>MUTAGEN</b>
Yes	<b>IRRITANT</b>	Yes	<b>TARGET ORGAN</b>

**13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Determine compliance status with all applicable requirements prior to disposal.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)**

<b>PROPER SHIPPING NAME:</b>	Xylene
<b>HAZARD CLASS:</b>	3
<b>UN/NA:</b>	UN1993
<b>LABELS:</b>	3 Flammable Liquid
<b>PACKING GROUP:</b>	III

**15. REGULATORY INFORMATION****SARA SECTION 313 - TOXIC CHEMICALS:**

This product does contain toxic chemicals under SARA Section 313 and 40 CFR Part 372.

<b>COMPONENTS</b>	<b>CAS #</b>	<b>%</b>
Xylene	1330-20-7	~2-4.5
Ethyl Benzene	100-41-4	~.75-1.5
Naphthalene	91-20-3	Less than 1

**SARA SECTION 311 - HAZARD CATEGORIES:**

This product may meet one or more of the criteria for the hazard categories defined in 40 CFR Part 370 as established by Sections 311 and 312 of SARA as indicated below:

Yes	<b>IMMEDIATE (ACUTE) HEALTH HAZARD</b>	No	<b>SUDDEN RELEASE OF PRESSURE HAZARD</b>
Yes	<b>DELAYED (CHRONIC) HEALTH HAZARD</b>	No	<b>REACTIVE HAZARD</b>
Yes	<b>FIRE HAZARD</b>	No	<b>PRESSURE</b>

**SARA SECTION 302 - EXTREMELY HAZARDOUS WASTE:**

This product is not known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

**CLEAN WATER ACT (CWA):**

Under the CWA, discharges of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8802.

**CERCLA HAZARDOUS SUBSTANCES:**

As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as a hazardous substance.

**U.S. TSCA INVENTORY**

All components of this material are on the U.S. TSCA Inventory or are not required to be listed on the U.S. TSCA Inventory

**16. OTHER INFORMATION**

THE INFORMATION IN THIS MATERIAL SAFETY DATA SHEET SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. WE BELIEVE THIS INFORMATION TO BE RELIABLE AND UP TO DATE AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS.

<b>NFPA HAZARD RATING</b>	least - 0	slight - 1	moderate - 2	high - 3	extreme - 4
---------------------------	-----------	------------	--------------	----------	-------------